


# BCR2PM

BCR 2PM


LOW POWER USE  
INSULATED TYPE, PLANAR PASSIVATION TYPE

**BCR2PM**



- IT (RMS) ..... 2A
- VDRM ..... 600V
- IRGT I, IRGT III ..... 10mA

**OUTLINE DRAWING** Dimensions in mm



① T1 TERMINAL  
② T2 TERMINAL  
③ GATE TERMINAL

TO-220F

## APPLICATION

Switching mode power supply, light dimmer, electric flasher unit, control of household equipment such as TV sets · stereo · refrigerator · washing machine · infrared kotatsu · carpet, solenoid drivers, small motor control, copying machine, electric tool, other general purpose control applications

## MAXIMUM RATINGS

Symbol	Parameter	Voltage class		Unit
		12	600	
VDRM	Repetitive peak off-state voltage *1	600		V
VDSM	Non-repetitive peak off-state voltage *1	720		V

Symbol	Parameter	Conditions	Ratings	Unit
IT (RMS)	RMS on-state current	Commercial frequency, sine full wave 360° conduction	2	A
ITSM	Surge on-state current	60Hz sinewave 1 full cycle, peak value, non-repetitive	10	A
I <sup>2</sup> <sub>t</sub>	I <sup>2</sup> <sub>t</sub> for fusing	Value corresponding to 1 cycle of half wave 60Hz, surge on-state current	0.41	A <sup>2</sup> s
PGM	Peak gate power dissipation		1	W
PG (AV)	Average gate power dissipation		0.1	W
VGM	Peak gate voltage		6	V
IGM	Peak gate current		1	A
T <sub>j</sub>	Junction temperature		-40 ~ +125	°C
T <sub>stg</sub>	Storage temperature		-40 ~ +125	°C
—	Weight	Typical value	2.0	g

\*1. Gate open.

# BCR2PM

LOW POWER USE


INSULATED TYPE, PLANAR PASSIVATION TYPE

## ELECTRICAL CHARACTERISTICS



Symbol	Parameter	Test conditions	Limits			Unit
			Min.	Typ.	Max.	
IDRM	Repetitive peak off-state current	$T_j=125^\circ\text{C}$ , $V_{\text{DRM}}$ applied	—	—	0.5	mA
VTM	On-state voltage	$T_a=25^\circ\text{C}$ , $I_{\text{TM}}=1.5\text{A}$ , Instantaneous measurement	—	—	1.6	V
VRGT I	Gate trigger voltage *2	$T_j=25^\circ\text{C}$ , $V_D=6\text{V}$ , $R_L=6\Omega$ , $R_G=330\Omega$	—	—	2.0	V
VRGT III			—	—	2.0	V
IRGT I	Gate trigger current *2	$T_j=25^\circ\text{C}$ , $V_D=6\text{V}$ , $R_L=6\Omega$ , $R_G=330\Omega$	—	—	10	mA
IRGT III			—	—	10	mA
VGD	Gate non-trigger voltage	$T_j=125^\circ\text{C}$ , $V_D=1/2V_{\text{DRM}}$	0.1	—	—	V
Rth (j-a)	Thermal resistance	Junction to ambient, Natural convection	—	—	40	$^\circ\text{C/W}$

\*2. Measurement using the gate trigger characteristics measurement circuit.

## GATE TRIGGER CHARACTERISTICS TEST CIRCUITS




## PERFORMANCE CURVES




# BCR2PM

LOW POWER USE  
INSULATED TYPE, PLANAR PASSIVATION TYPE


**GATE CHARACTERISTICS**




**GATE TRIGGER CURRENT VS. JUNCTION TEMPERATURE**




**GATE TRIGGER VOLTAGE VS. JUNCTION TEMPERATURE**




**MAXIMUM TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS (JUNCTION TO AMBIENT)**



**MAXIMUM ON-STATE POWER DISSIPATION**



**ALLOWABLE AMBIENT TEMPERATURE VS. RMS ON-STATE CURRENT**



# BCR2PM

LOW POWER USE  
INSULATED TYPE, PLANAR PASSIVATION TYPE

