

NPN power transistor

Features

■ NPN transistor

Applications

■ General purpose switching

Description

The device is manufactured in Planar technology with "Base Island" layout. The resulting transistor shows exceptional high gain performance coupled with very low saturation voltage.

ypsolete Product(s)




Figure 1. Internal schematic diagram




Table 1. Device summary

Order code	Marking	Package	Packaging
BD179	BD179	SOT-32	Tube

Electrical ratings BD179

1 Electrical ratings

2/9

Table 2. Absolute maximum rating

- 400.0 -			
Symbol	Parameter	Value	Uni
V _{CBO}	Collector-base voltage (I _E = 0)	80	V
V _{CEO}	Collector-base voltage (I _B = 0)	80	V
V _{EBO}	Emitter-base voltage (I _C = 0)	5	V
I _C	Collector current	3	Α
I _{CM}	Collector current current (t _p < 5ms)	7	A
I _B	Base current	1	A
P _{TOT}	Total dissipation at T _{case} = 25°C	30	W
T _{stg}	Storage temperature	-65 to 150	°C
T_J	Max. operating junction temperature	150	0.0
	Obsolet	S	°C
	Storage temperature Max. operating junction temperature		

2 Electrical characteristics

(T_{case} = 25°C unless otherwise specified)

Table 3. Electrical characteristics


Symbol	Parameter	Test Conditions	Min.	Тур.	Max.	Unit
I _{CBO}	Collector cut-off current (I _E = 0)	V _{CB} = 80V			0.1	mA
I _{EBO}	Emitter cut-off current (I _C = 0)	V _{EB} = 5V			1 ,	mA
V _{CEO(sus)} (1)	Collector-emitter sustaining voltage (I _B = 0)	I _C =100mA	80	UC		V
V _{CE(sat)} (1)	Collector-emitter saturation voltage	$I_C = 1A$ $I_B = 0.1A$	(0,		0.8	V
V _{BE} ⁽¹⁾	Base-emitter voltage	$I_C = 1.5A$ $V_{CE} = 2V$			1.3	٧
h _{FE}	DC current gain	$I_C = 150 \text{mA}$ $V_{CE} = 2V$ $I_C = 1 \text{A}$ $V_{CE} = 2V$	40 15			

Note (1) Pulsed duration = 300 μs, duty cycle ≤1.5%

2.1 Electrical characteristic (curves)

Figure 2. Safe operating area


Figure 3. Derating curve



Electrical characteristics BD179

Figure 4. DC current gain

Figure 5. DC current gain







Figure 6. Collector-emitter saturation voltage

Figure 7. Base-emitter saturation voltage








Figure 8. Base-emitter on voltage

Figure 9. Resistive load switching time





4/9





Figure 10. Resistive load switching time

2.2 **Test circuits**

Figure 11. Resistive load switching test circuit



3 Package mechanical data


In order to meet environmental requirements, ST offers these devices in ECOPACK® packages. These packages have a Lead-free second level interconnect. The category of second level interconnect is marked on the package and on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label. ECOPACK is an ST trademark. ECOPACK specifications are available at: www.st.com

Obsolete Product(s). Obsolete Product(s)

577

SOT-32 (TO-126) MECHANICAL DATA

DIM.	mm.				
DIM.	MIN.	TYP	MAX.		
Α	2.4		2.9		
В	0.64		0.88		
B1	0.39		0.63		
D	10.5		11.05		
E	7.4		7.8		
е	2.04	2.29	2.54		
e1	4.07	4.58	5.08		
L	15.3		16		
Р	2.9	X	3.2		
Q		3.8			
Q1	1	18	1.52		
H2		2.15			
I		1.27			



577

Revision history BD179

4 Revision history

Table 4. Revision history

Date	Revision	Changes
01-Dec-2000	1	Initial release.
02-Jul-2007	2	Figures 2,3,4,5,6,7, 8, 9 and figure 10 have been added.

Obsolete Product(s). Obsolete Product(s)

8/9

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZE REPRESENTATIVE OF ST, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS, WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

 ${\rm ST}$ and the ${\rm ST}$ logo are trademarks or registered trademarks of ${\rm ST}$ in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2007 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com

